

PRODUCT SPECIFICATIONS

enduro

Total thickness	EN-ISO 24346	4.0 mm
Wear layer thickness	EN-ISO 24340	0.30 mm
Collection size		20
Domestic use	EN-ISO 10874	23
Commercial use	EN-ISO 10874	31
Tile size	EN-ISO 24342	30.5 x 61 cm
Plank size	EN-ISO 24342	18.5 x 121.2 cm
Packaging per carton tiles		2.23 m ² (12 pcs)
Packaging per carton planks		2.24 m ² (10 pcs)
Squareness and straightness	EN-ISO 24342	< 400 mm < 0.25 mm > 400 mm < 0.35 mm
Total weight	ISO 23997	ca. 6700 g/m ²
Wear layer Binder Content	EN-ISO 10582	Type 1
Slip resistance	DIN 51130 EN 13893	R10 DS - $\mu > 0.30$
Acoustical impact noise reduction	EN-ISO 717-2	6 dB without / 15 dB with Forbo underlay
Castor chair continuous use	ISO 4918	Good
Residual indentation	ISO 24343-1	≤ 0.10 mm
Light fastness	ISO 105-B02	≥ 6
VOC emissions reaction to fire	EN-ISO 160009	≤ 100 µg/m ³
Resistance to chemicals	ISO 26987	Good
Dimension stability	EN-ISO 23999	≤ 0.10%
Fire resistance	EN 13501	Bfl-s1, L, NCS with and without Forbo underlay
Thermal conductivity	ISO 8302	0.25 W/mK
Body voltage	EN 1815	< 2 kV

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
 All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
 The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



FLOORING SYSTEMS